


LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
ILLUMINAZIONE ABITAZIONI LAMPADINE A BULBO AC 220V												
1		H0033	1	37x112mm	AC 110-240V	3W	White 5500k Warm 2700k	360°	160-180lm	E14	Bridgelux	25-30W incandescenza
2		H005	3	38x105mm	AC 85-265V	3W	White 5000-7000K Warm white 3000-3500K	360°	210-240lm	E14	Epistar	30W incandescenza
3	 certificazione fotobiologica	H0094	4	60x115mm	AC 85-260V	4W	White 6000k Warm 2700k	160°	260-290lm	E27	Samsung	40W incandescenza
4	 certificazione fotobiologica	H0096	4	60x115mm	AC 85-260V	6W	White 6000k Warm 2700k	160°	400-450lm	E27	Samsung	50W incandescenza
5	 certificazione fotobiologica	H0098	4	60x117mm	AC 85-260V	8W	White 6000k Warm 2700k	160°	650lm	E27	Samsung	55W incandescenza






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
6	 certificazione fotobiologica	H00910	4	60x117mm	AC 180-240V	10W	White 6000k Warm 2700k	160°	790-850lm	E27	Samsung	70W incandescenza
7		H0103	3	46.5x85mm	AC 85-260V	3W	White 6000k Warm 3000k	360°	300lm	E14	Edison	25W incandescenza
8		H0104	\	60x117mm	AC 85-260V	4W	White 6000k Warm 3000k	180°	290-260lm	E14	Epistar	40W incandescenza
9		H0105	\	60x117mm	AC 85-260V	6W	White 6000k Warm 3000k	180°	450-400lm	E27	Epistar	60W incandescenza
10		H0108	\	60x117mm	AC 85-260V	8W	White 6000k Warm 3000k	180°	650-580lm	E27	Epistar	70W incandescenza





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
11		H0111	36	46.5x68mm	AC 180-240V	1.5W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	120lm	E14/ E27		25W incandescenza
12		H0112	60	46.5x85mm	AC 180-240V	2.5W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	200lm	E14/ E27		30W incandescenza
13		H0114	96	46.5x102mm	AC 180-240V	4W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	320lm	E14/ E27		40W incandescenza
14		H0116	156	46.5x147mm	AC 180-240V	6W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	480lm	E14/ E27		45W incandescenza
15		H0118	192	46.5x173mm	AC 180-240V	8W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	640lm	E14/ E27		50W incandescenza
16		H01215	288	90x139mm	AC 180-240V	15W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	1200lm	E27/ E40		85W incandescenza





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
17		H01220	384	90x160mm	AC 180-240V	20W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	1600lm	E27/ E40		100W incandescenza
18	LAMPADINE A BULBO DC 12V											
19		H013	60	43x125mm	12V DC	5W	White 6000-6500K Warm white 3000-3500K	360°	320-360lm 250-290lm	E27		40W incandescenza
20		H014	144	58x140mm	12V DC	8W	White 6000-6500K Warm white 3000-3500K	360°	650-860lm 510-700lm	E27		75W incandescenza
21	LAMPADE A LED BULBO ALTA POTENZA											
22		H01525	512	90x194mm	AC 180-240V	25W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	2000lm	E27/ E40		110W incandescenza
23		H01530	576	90.5x223mm	AC 180-240V	30W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	2400lm	E27/ E40		150W incandescenza

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
24		H01535	640	90.5x223mm	AC 180-240V	35W	W 5000-6000K NW 4000-4500K WW 2800-3500K	360°	2800lm	E27/ E40		200W inc/ 100W SAP
25	LAMPADINE A BULBO RGB											
26		H016	1	60x125mm	220V AC	5W	RGB	360°	30lm (red), 15lm (blue), 60 lm (green)	E27	Epistar	\
27	LAMPADE A LED ATTACCO G24 2 PINS E 4 PINS											
28		H0175	20	35x60mm	AC 100-265V	5W	White 6000~6500K C. White 4000- 4500K WW 3000~3200K	120°	500/400lm	G24 2 PINS OR 4 PINS	Bridgelux SMD 5050	45W incandescenza
29		H0178	36	35x116mm	AC 100-265V	8W	White 6000~6500K C. White 4000- 4500K WW 3000~3200K	120°	800/650 Lm	G24 2 PINS OR 4 PINS	Bridgelux SMD 5050	55W incandescenza






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
30		H01711	60	35x156mm	AC 100-265V	11W	White 6000~6500K C. White 4000-4500K WW 3000~3200K	>120°	1250/950Lm	G24 2 PINS OR 4 PINS	Bridgelux SMD 5050	85W incandescenza
31		H0185	4	114x40x40mm	AC 85-265V	5W	White 6000~7000K C. White 4000-4500K WW 2800~3500K	160°	360-400lm	G24 2 PINS OR 4 PINS	Epistar	40W incandescenza
32		H0187	6	144x40x40mm	AC 85-265V	7W	White 6000~7000K C. White 4000-4500K WW 2800~3500K	160°	540-600lm	G24 2 PINS OR 4 PINS	Epistar	50W incandescenza
33		H0189	8	176x40x40mm	AC 85-265V	9W	White 6000~7000K C. White 4000-4500K WW 2800~3500K	160°	720-800lm	G24 2 PINS OR 4 PINS	Epistar	65W incandescenza

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
34	LAMPADINE A BULBO DIMMERABILI											
35	 certificazione fotobiologica	H0196	4	60x115mm	AC 85-260V	6W	White 6000k Warm 2700k	160°	400-450lm	E27	Samsung	50W incandescenza
36	 certificazione fotobiologica	H0198	4	60x115mm	AC 85-260V	8W	White 6000k Warm 2700k	160°	580lm	E27	Samsung	55W incandescenza
37	 certificazione fotobiologica	H01910	4	60x115mm	AC 85-260V	10W	White 6000k Warm 2700k	160°	790-850lm	E27	Samsung	70W incandescenza
38	LAMPADINA A BULBO DIMMERABILE+ TELECOMANDO A 4 CANALI: 1 TELECOMANDO Può COMANDARE CONTEMPORANEAMENTE Più LAMPADINE											
39		H0196T	4	60x115mm	AC 85-265V	6W	White 6500k Warm 3000k	180°	560lm	E27	Epistar	55W incandescenza

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
40		H019T	\	Telecomando per lampadine AL REMB-D 6W, il telecomando ha 4 canali può controllare più lampadine o più gruppi di lampadine contemporaneamente. Le funzioni principali sono le seguenti: aumenta/diminuisce intensità luce, cambia colore (da 3000 a 6500K) alle lampadine, funzione NIGHT (luce soffusa per la notte), funzione standby. Istruzioni incluse, non serve modificare il portalampada o installare alcun dimmer.								
41	FARETTI LED ALTA POTENZA LED SERIE HALOGEN GREEN (DISPONIBILI DIMMERABILI SU RICHIESTA)											
42		F00205G	1	50x71mm	100-240V AC	5W	WW:2700-3000K PW:6000-6500K	24/38/60°	WW:350-360lm PW:400-430lm	GU10	CRI WW:80 PW:75	50W alogeno
43		F00205M	1	50x63mm	12V AC/DC	5W	WW:2700-3000K PW:6000-6500K	24/38/60°	WW:350-360lm PW:400-430lm	MR16	CRI WW:80 PW:75	50W alogeno
44		F00207G	1	50x100mm	100-240V AC	7W	WW:2700-3000K PW:6000-6500K	24/38/60°	WW:490-500lm PW:500-560lm	GU10	CRI WW:80 PW:75	65W alogeno
45		F00207M	1	50x92mm	12V AC/DC	7W	WW:2700-3000K PW:6000-6500K	24/38/60°	WW:490-500lm PW:500-560lm	MR16	CRI WW:80 PW:75	65W alogeno

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
46		F00209G	1	50x110mm	100-240V AC	9W	WW:2700-3000K PW:6000-6500K	24/38/60°	WW:630-650lm PW:720-750lm	GU10	CRI WW:80 PW:75	75W alogeno
47		F00209M	1	50x102mm	12V AC/DC	9W	WW:2700-3000K PW:6000-6500K	24/38/60°	WW:630-650lm PW:720-750lm	MR16	CRI WW:80 PW:75	75W alogeno
48	Faretti MEDIUM SERIES MR16/GU10											
49		F006M	1	50X55mm	12V AC/DC	4W	White 6000K Warm White 3000K	30/60°	270lm	MR16	Epistar	50W alogeno
50		F006G	1	50X56mm	110-220V AC	4W	White 6000K Warm White 3000K	30/60°	270lm	GU10	Epistar	50W alogeno
51												
52		F007M	5	50x80mm	12V AC/DC	4W	2800/4000/5000/ 6500-7000K	60°	420-450lm	MR16		50W alogeno

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
53		F007G	5	50x87mm	220V AC	4W	2800/4000/5000/ 6500-7000K	60°	420-450lm	GU10		50W alogeno
54	Faretti MEDIUM SERIES MR16/GU10											
55		F008M	3	50x52mm	12V AC/DC	3W	White 6000K Warm White 3000K	30°	230lm	MR16	Genesis	30W alogeno
56		F008G	3	50x60mm	220V AC	3W	White 6000K Warm White 3000K	30°	230lm	GU10	Genesis	30W alogeno
57	FARETTI RGB											
58		F009M	1	50x57mm	12V DC	5W	RGB	60°	30lm (red), 15lm (blue), 60 lm (green)	MR16	Epistar	\
59		F009G	1	50x68mm	220V AC	5W	RGB	60°	30lm (red), 15lm (blue), 60 lm (green)	GU10	Epistar	\



LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
60	LAMPADE PAR, AR111											
61		P001	7	67x111mm	12V AC/DC	8W	White 6000K Warm White 3000K	35°	670-740lm	AR111 GX53	CREE	70W incandescenza
62		P002	7	95x96mm	AC 85-260V	8W	White 6000K Warm White 3000K	35°	670-740lm	E27	Epistar	50W incandescenza
63		P003	12	118x126mm	AC 85-260V	14W	White 6000K Warm White 3000K	35°	1200-1350lm	E27	Epistar	85W incandescenza
64	LAMPADE A LED R7S											
65		P0095	24	78x54mm	AC85-265V	5W	Pure White 4000- 5000K/Warm White 2800- 3000K	200°	430-450lm	R7S	Epistar	36W incandescenza
66		P0098	36	118x54mm	AC85-265V	8W	Pure White 4000- 5000K/Warm White 2800- 3000K	200°	650-700lm	R7S	Epistar	60W incandescenza



LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
67		P00910	42	118x54mm	AC85-265V	10W	Pure White 4000-5000K/Warm White 2800-3000K	200°	800-850lm	R7S	Epistar	70W incandescenza
68		P00913	60	189x54mm	AC85-265V	13W	Pure White 4000-5000K/Warm White 2800-3000K	200°	1050-1100lm	R7S	Epistar	90W incandescenza
69		P00915	72	189x54mm	AC85-265V	15W	Pure White 4000-5000K/Warm White 2800-3000K	200°	1300-1350lm	R7S	Epistar	110W incandescenza
70	LED SPOT LIGHT FARETTI DA ESTERNO IP65 LED MODULARE EPISTAR ALTA RESA LUMINOSA											
71		P010	1	9x11,5x8,5 cm	100-240V AC	10W	White 6000k Warm White 3000K	120°	800lm	Cavo IP65	Bridgelux	70W alogeno
72		P01110	1	9x11,5x8,5 cm	AC85-265V	10W	White 6000k Warm White 3000K	120°	800lm	Cavo IP65	Epistar	70W alogeno






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
73		P01120	1	18x14x10 cm	AC85-265V	20W	White 6000k Warm White 3000K	120°	1600lm	Cavo IP65	Epistar	100W I.M.
74		P01130	1	19x23x13 cm	AC85-265V	30W	White 6000k Warm White 3000K	120°	2400 lm	Cavo IP65	Epistar	150W I.M.
75		P01150	1	23x28x15 cm	AC85-265V	50W	White 6000k Warm White 3000K	120°	4000lm	Cavo IP65	Epistar	250W I.M.
76		P01280	1	36x27x12cm	AC85-265V	80W	White 6000k Warm White 3000K	120°	6400lm	Cavo IP65	Epistar	300W I.M.
77		P014100	2	66x26x36cm	AC85-265V	100W	White 5500-6000k / Warm White 3000-3500K	120°	9000-10000lm	Cavo IP65	Bridgelux	350W I.M.
78		P014120	2	66x26x36cm	AC85-265V	120W	White 5500-6000k / Warm White 3000-3500K	120°	10800-12000lm	Cavo IP65	Bridgelux	400W I.M.






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
79		P014140	2	66x26x36cm	85-264V AC	140W	White 5500-6000k / Warm White 3000-3500K	120°	12600-14000lm	Cavo IP65	Bridgelux	400W I.M.
80	FARETTI LEDLINE DA ESTERNO IP65 LED MODULARE EPISTAR ALTA RESA LUMINOSA DESIGN INNOVATIVO											
81		P01610	1	9x11,5x8,5 cm	85-265V AC	10W	White 6000k Warm White 3000K	120°	700lm	Cavo IP65	Chimei	70W alogeno
82		P01620	1	18x14x10 cm	85-265V AC	20W	White 6000k Warm White 3000K	120°	1400lm	Cavo IP65	Chimei	100W I.M.
83		P01630	1	19x23x13 cm	85-265V AC	30W	White 6000k Warm White 3000K	120°	2100lm	Cavo IP65	Chimei	150W I.M.
84		P01650	1	23x28x15 cm	85-265V AC	50W	White 6000k Warm White 3000K	120°	3500lm	Cavo IP65	Chimei	250W I.M.






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
85		P01670	1	36x27x12cm	85-265V AC	70W	White 6000k Warm White 3000K	120°	4900lm	Cavo IP65	Chimei	300W I.M.
86	ILLUMINAZIONE STRADALE LED CREE/Philips lumileds											
87		S012	14	\	85-135VAC 187-264VAC 250-305VAC 12-24VDC	18W	WW:3000K PW:4500K CW:5700K	140° rectangular beam	1350lm	Cavo Ip65	Philips lumileds	40W HPS
88		S013	24	\	85-135VAC 187-264VAC 250-305VAC 12-24VDC	30W	WW:3000K PW:4500K CW:5700K	140° rectangular beam	2200lm	Cavo Ip65	Philips lumileds	65W HPS
89		S014	30	\	85-135VAC 187-264VAC 250-305VAC 12-24VDC	35W	WW:3000K PW:4500K CW:5700K	140° rectangular beam	2700lm	Cavo Ip65	Philips lumileds	70W HPS
90		S015	38	\	85-135VAC 187-264VAC 250-305VAC 12-24VDC	48W	WW:3000K PW:4500K CW:5700K	140° rectangular beam	3600lm	Cavo Ip65	Philips lumileds	130W HPS






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\phi \times H$	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
91		S001	24	269×110×80mm	85-264VAC 12VDC 24VDC	30W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	120/140(rectangular beam)	2500lm	E27/E40	CREE	70W HPS
92		S002	48	565×380×160mm	85-264VAC 12VDC 24VDC	48W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	120/140(rectangular beam)	5136lm	Fissaggio su palo IP65	CREE	150W HPS
93		S003	96	680×380×160mm	85-264VAC 24VDC	96W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	120/140(rectangular beam)	10272lm	Fissaggio su palo IP65	CREE	250W HPS
94	ILLUMINAZIONE INDUSTRIALE LED BRIDGELUX e alimentatore MEANWELL											
95		I00145	1	350 ϕ *286mm	85-260VAC	45W	White 6000K Warm white 3000K	140°	3150lm	Cavo	Epistar	250W I.M. 6m h
96		I00170	1	457 ϕ *347mm	85-260VAC	70W	White 6000K Warm white 3000K	140°	4900lm	Cavo	Epistar	250W I.M. 6m h
97		I00190	1	532 ϕ *282mm	85-260VAC	90W	White 6000K Warm white 3000K	140°	6300lm	Cavo	Epistar	400W I.M. 6m h




















































































LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
98		I001150	1	580Φ*428mm	85-260VAC	150W	White 6000K Warm white 3000K	140°	10500lm	Cavo	Epistar	400W I.M. 8m h
99	ILLUMINAZIONE INDUSTRIALE LED CREE/PHILIPS LUMILEDS ALTA POTENZA E RESA LUMINOSA 107-122 lm/w											
100		I00528	28	368x385x250mm	85-264V AC	28W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Verticale 90°	1950lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	
101		I00542	42	1270x130x160mm	85-264V AC	42W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Verticale 90°	3500lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	250W I.M.
102		I006	28	368x385x250mm	85-264V AC	50W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Verticale 90°	4000lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	250W I.M.
103		I00775	42	368x385x250mm	85-264V AC	75W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Verticale 90°	6100lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	



















































































LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
104		I007100	56	455x385x250m m	85-264V AC	100W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Ver ticale 90°	8100lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	
105		I007125	70	540x385x250m m	85-264V AC	125W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Ver ticale 90°	10100lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	
106		I007150	84	626x471x336m m	85-264V AC	150W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Ver ticale 90°	12100lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	
107		I007175	98	724x397x265m m	85-264V AC	175W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Ver ticale 90°	14100lm	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	
108		I007200	112	744x329x219m m	85-264V AC	200W	Ww 2700-3500K Pw 4000-5000K Cw 5000-6500K	Orizz. 100°/Ver ticale 90°	16200	Cavo IP66	CREE/PHIL IPS LUMILEDS REBEL	
109	WALLWASHER (FARI A LED ILLUMINAZIONE FACCIATE DI PALAZZI, STATUE ED EFFETTI LUMINOSI ALL'ESTERNO)											

















































































LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza														
110		I002	36	280x140x70mm	AC100-240V 50-60hz	36W	<table border="1" style="font-size: 8px;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		50°	\	Cavo IP65	\	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
111		I003	48	685x140x138mm	AC100-240V 50-60hz	48W	<table border="1" style="font-size: 8px;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		50°	\	Cavo IP65	\	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
112		I004	72	685x140x138mm	AC100-240V 50-60hz	72W	RGB	50°	\	Cavo IP65	\	\														
113	BOBINE 5 METRI STRISCIA LED SMD 5050 30 LED A METRO																									
114	 certificazione fotobiologica	R001	150	5m/ Roll	12VDC	36W/Roll (7.2w/m)	<table border="1" style="font-size: 8px;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> <tr><td>RGB</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		RGB		120°	no water prof		Epistar SMD 5050	\
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
RGB																										
115	 certificazione fotobiologica	R001W	150	5m/ Roll	12VDC	36W/Roll (7.2w/m)	<table border="1" style="font-size: 8px;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> <tr><td>RGB</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		RGB		120°	minitrsparent silicon tube(IP67) or Epoxy filled (IP68)	IP67/IP68	Epistar SMD 5050	\
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
RGB																										
116	BOBINE 5 METRI STRISCIA LED SMD 5050 60 LED A METRO																									





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	lm	Base	LED Brand	Corrispondenza														
117	 certificazione fotobiologica	R002	300	5m/ Roll	12VDC	72W/ Roll (14.4 w/m)	<table border="1"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		120°	no water proof		Epistar SMD 5050	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
118	 certificazione fotobiologica	R002W	300	5m/ Roll	12VDC	72W/ Roll (14.4 w/m)	<table border="1"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		120°	minitrsparent silicon tube(IP67) or Epoxy filled (IP68)	IP67/IP 68	Epistar SMD 5050	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
119	BOBINE 5 METRI STRISCIA LED SMD 3528 60 PCS LED A METRO																									
120	 certificazione fotobiologica	R003	300	5m/ Roll	12VDC	24W/ Roll (4.8 w/m)	<table border="1"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> <tr><td>RGB</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		RGB		120°	no water proof		Epistar SMD 3528	\
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
RGB																										
121	 certificazione fotobiologica	R003W	300	5m/ Roll	12VDC	24W/ Roll (4.8 w/m)	<table border="1"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> <tr><td>RGB</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		RGB		120°	minitrsparent silicon tube(IP67) or Epoxy filled (IP68)	IP67/IP 68	Epistar SMD 3528	\
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
RGB																										
122	BOBINE 5 METRI STRISCIA LED SMD 3528 120 PCS A METRO																									







LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times$ H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza														
123	 certificazione fotobiologica	R004	600	5m/ Roll	12VDC	48W/Roll (9.6 w/m)	<table border="1" style="font-size: small;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		120°	no water proof		Epistar SMD 3528	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
124	 certificazione fotobiologica	R004W	600	5m/ Roll	12VDC	48W/Roll (9.6 w/m)	<table border="1" style="font-size: small;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		120°	minitrsparent silicon tube(IP67) or Epoxy filled (IP68)	IP67/IP 68	Epistar SMD 3528	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
125	BOBINE 5 METRI STRISCIA LED SMD 3528 E 5050 60 PCS A METRO 220V IP67 (Non si possono utilizzare sott'acqua)																									
126		R01120	300	5m/ Roll	110-220V AC	20W/Roll (4w/m)	<table border="1" style="font-size: small;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		120°	1800lm/roll	IP67	Epistar SMD 3528 6lm/LED	\		
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
127		R01160	300	5m/ Roll	110-220V AC	60W/Roll (12w/m)	<table border="1" style="font-size: small;"> <tr><td>Red</td><td></td></tr> <tr><td>Yellow</td><td></td></tr> <tr><td>Blue</td><td></td></tr> <tr><td>White</td><td></td></tr> <tr><td>Warm White</td><td></td></tr> <tr><td>Green</td><td></td></tr> <tr><td>RGB</td><td></td></tr> </table>	Red		Yellow		Blue		White		Warm White		Green		RGB		120°	6000lm/roll	IP67	Epistar SMD 5050 12lm/LED	\
Red																										
Yellow																										
Blue																										
White																										
Warm White																										
Green																										
RGB																										
128		RA010	\	\	\	\	alimentatore strisce 220V			\	\	\														

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza												
129		R0114	60/m	\	110-220V AC	4W/m	<table border="1" style="font-size: small;"> <tr><td>Red</td><td>■</td></tr> <tr><td>Yellow</td><td>■</td></tr> <tr><td>Blue</td><td>■</td></tr> <tr><td>White</td><td>■</td></tr> <tr><td>Warm White</td><td>■</td></tr> <tr><td>Green</td><td>■</td></tr> </table>	Red	■	Yellow	■	Blue	■	White	■	Warm White	■	Green	■	120°	360lm/m	IP67	Epistar SMD 3528 6lm/LED	\
Red	■																							
Yellow	■																							
Blue	■																							
White	■																							
Warm White	■																							
Green	■																							
130		R01112	60/m	\	110-220V AC	12W/m		120°	1200lm/m	IP67	Epistar SMD 5050 6lm/LED	\												
131		RA011	\	\	\	\	connettore strisce 220V			\	\	\												
132		RA012	\	\	\	\	connettore strisce 220V			\	\	\												
133		RA013	\	\	\	\	alimentatore strisce 220V			\	\	\												
134	ACCESSORI PER STRISCE A LED																							






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times$ H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
141		RA005										Giunto per collegamento strisce LED tagliate
142		RA00618										Alimentatore 12V per strisce LED rigide touch 18W
143		RA00636										Alimentatore 12V per strisce LED rigide touch 36W
144		RA007										4 pcs magnete per strisce LED rigide touch
145		RA008										Connettore strisce LED rigide touch 15cm
146		RA009										Connettore strisce LED rigide touch





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
147	STRISCE Touch A LED RIGIDE LED SMD 5050 per Vettrine											
148		R0079	36	600x20x14,2m m	12V DC	9W	White 6000K Warm White 3000K	\	540-480lm	cavo	Epistar SMD 5050	\
149		R00715	60	1000x20x14,2m m	12V DC	14W	White 6000K Warm White 3000K	\	850-750lm	cavo	Epistar SMD 5050	\
150	STRISCE Touch A LED RIGIDE LED SMD 3528 per Vettrine											
151		R00810	123	600x20x14,2m m	12V DC	10W	White 6000K Warm White 3000K	\	650-600lm	cavo	Epistar SMD 3528	\
152		R00816	213	1000x20x14,2m m	12V DC	16W	White 6000K Warm White 3000K	\	1000-900lm	cavo	Epistar SMD 3528	\
153	STRISCE LED 3528 IN ALLUMINIO 12 V IP65 per vetrine											
154		R0094C	45	500x8x1,6mm	12V DC	4W	6000-7000K	120°	270lm	cavo	Epistar SMD 3528	IP40

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times$ H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
155		R0094H	45	500x8x1,6mm	12V DC	4W	3000-3500K	120°	270lm	cavo	Epistar SMD 3528	IP40
156		R0098C	90	1000x8x1,6mm	12V DC	7,5W	6000-7000K	120°	540lm	cavo	Epistar SMD 3528	IP40
157		R0098H	90	1000x8x1,6mm	12V DC	7,5W	3000-3500K	120°	540lm	cavo	Epistar SMD 3528	IP40
158	STRISCE LED 5060 IN ALLUMINIO 12 V IP65 per vetrine											
159		R0106C	30	500x8x1,6mm	12V DC	6W	6000-7000K	120°	600lm	cavo	Epistar SMD 5060	IP65
160		R0106H	30	500x8x1,6mm	12V DC	6W	3000-3500K	120°	600lm	cavo	Epistar SMD 5060	IP65





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
161		R01012C	60	1000x8x1,6mm	12V DC	12W	6000-7000K	120°	1200lm	cavo	Epistar SMD 5060	IP65
162		R01012H	60	1000x8x1,6mm	12V DC	12W	3000-3500K	120°	1200lm	cavo	Epistar SMD 5060	IP65
163	TUBI A LED T8 Con certificazione per il rischio fotobiologico EN62471 COMPATIBILI CON REATTORE, NON OCCORRE TOGLIERE IL REATTORE, (Fase e neutro dalla stessa estremità)											
164	 certificazione fotobiologica	T0029	132	600mm	AC110-240V	9W	Commercial White (4500K)	120°	900lm±15% transparent cover	T8	SMD LED 3528	Tubo Neon 18W
165	 certificazione fotobiologica	T00213	192	900mm	AC110-240V	13W	Commercial White (4500K)	120°	1300lm±15% transparent cover	T8	SMD LED 3528	Tubo neon 25W

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
166	 certificazione fotobiologica	T00218	264	1200mm	AC110-240V	18W	Commercial White (4500K)	120°	1750lm±15% transparent cover	T8	SMD LED 3528	Tubo neon 36W
167	 certificazione fotobiologica	T00222	312	1500mm	AC110-240V	22W	Commercial White (4500K)	120°	2080lm±15% transparent cover	T8	SMD LED 3528	Tubo Neon 58W
168	TUBI LED (3014 & 3528 alta luminosità) disponibili sia con fase ad un'estremità e neutro dall'altra sia con fase e neutro da una sola estremità											
169		T02218	180 SMD 3014	1200mm	AC 85-265V	18W	Commercial White (4000-4500K)	120°	1950lm	T8	SMD LED 3014	Tubo Neon 36W
170	Cover opaca>	T022180	\	\	\	\	\	\	\	\	\	\
171		T02225	360 SMD 3528	1200mm	AC 85-265V	25W	Commercial White (4000-4500K)	120°	2400lm	T8	SMD LED 3528	Tubo Neon 36W
172	Cover opaca>	T022250	\	\	\	\	\	\	2000lm	\	\	\






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
173		T02323	220 SMD 3014	1500mm	AC 85-265V	23W	Commercial White (4000-4500K)	120°	2450lm	T8	SMD LED 3014	Tubo Neon 58W
174	Cover opaca>	T023230	\	\	\	\	\	\	\	\	\	\
175		T02328	432 SMD 3528	1500mm	AC 85-265V	28W	Commercial White (4000-4500K)	120°	2850lm	T8	SMD LED 3528	Tubo Neon 58W
176	Cover opaca>	T023280	\	\	\	\	\	\	2450lm	\	\	\
177	TUBI A LED T10 IP65 LED SMD 3014 resistenti all'acqua											
178		T02410	96	600mm	AC 85-265V	10W	Commercial White (4000-4500K)	120°	900lm±10% transparent cover	T10	SMD LED 3014	Tubo Neon 18W
179		T02418	216	1200mm	AC 85-265V	18W	Commercial White (4000-4500K)	120°	1700lm±10% transparent cover	T10	SMD LED 3014	Tubo Neon 36W





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
180		T02420	216	1500mm	AC 85-265V	20W	Commercial White (4000-4500K)	120°	2000lm±10% transparent cover	T10	SMD LED 3014	Tubo Neon 58W
181	TUBI A LED T5											
182		T0043	42	300mm	AC100-240V	3W	White 6000-6500K Warm white 2700-3200K	120°	210-250lm	T5	Epistar SMD	Tubo Neon T5 300mm
183		T0046	76	600mm	AC100-240V	6W	White 6000-6500K Warm white 2700-3200K	120°	380-456lm	T5	Epistar SMD	Tubo Neon T5 600mm
184		T0049	120	900mm	AC100-240V	9W	White 6000-6500K Warm white 2700-3200K	120°	600-720lm	T5	Epistar SMD	Tubo Neon T5 900mm
185		T00412	168	1200mm	AC100-240V	12W	White 6000-6500K Warm white 2700-3200K	120°	840-1008lm	T5	Epistar SMD	Tubo Neon T5 1200mm
186	LED PENDANT, TUBI LED E PLAFONIERE LEDLINE PARKING CON ATTACCHI A SOFFITTO											






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
187		T02535	72	1180x145x65 mm	AC85-265V	35W	White/Warm White	120°	2300lm	cavo	Samsung 5630	2 x Tubo neon 36W
188		T02545	96	1180x145x65 mm	AC85-265V	45W	White/Warm White	120°	2900lm	cavo	Samsung 5630	3 x Tubo neon 36W
189		T02575	144	1180x145x65 mm	AC85-265V	75W	White/Warm White	120°	4550lm	cavo	Samsung 5630	3 x Tubo neon 58W
190		T00518	280	1610mm	AC85-265V	18W	White 6000-7000K Warm white 3000-4000K Commercial White 4000-5000K	120°	1260LM±10%	cavo	SMD 3528	Tubo neon 36W
191		T00536	560	120x1200mm	AC85-265V	36W	White 6000-7000K Warm white 3000-4000K Commercial White 4000-5000K	120°	2520LM±10%	cavo	SMD 3528	2 x Tubo neon 36W






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
192	PANNELLI LED (PANNELLI LUMINOSI DA INCASSO NEL SOFFITTO) ILLUMINAZIONE UFFICI (DISP. ANCHE DIMMERABILI)											
193		T026		600x600mm	100-240V AC (Adapter incluso)	45W	3000-6000K	120°	2430-2568lm	cavo	Epistar	4x18W tubi neon
194			T027		300x600mm	100-240V AC (Adapter incluso)	45W	3000-6000K	120°	2430-2568lm	cavo	Epistar
195		T011	400	595x595x48mm	100-240V AC (Adapter incluso)	45W	Cool white 5700-7000k Naturalwhite 4000-5000k Warmwhite 2700-3300	160°	3500/3900lm	cavo	SMD3014	4x18W tubi neon
196		T012	676	300x1200x50mm	100-240V AC (Adapter incluso)	45W	Cool white 5700-7000k Naturalwhite 4000-5000k Warmwhite 2700-3300	120°	3800/4000lm	cavo		2x36W tubi neon





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
197	Pannelli LED con modulo d'emergenza, durata 3 ore 30% luminosità											
198		T028	400	595*595*48mm	AC85-265V (adapter incluso)	45W	Cool white 5700-7000k Naturalwhite 4000-5000k Warmwhite 2700-3300	120°	3500-3900lm	cavo	SMD3014	4x18W tubi neon
199		T029		Emergency driver Module, 30% luminosità per 3 ore								
200	Accessori pannelli LED											
201		T030		1 dimmer può controllare fino a 1500 pannelli mod. PL-0606-4504 dimmerabili, Dimmable range: 0-100%								
202	PANNELLI LED COLORATI E RGB											
203		T017	150	300x300mm	100-240V AC (Adapter incluso)	19W	blue, red, green, RGB (controller RGB incluso)	120°	\	cavo	Epistar	\





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
204		T018	400	300x1200mm	100-240V AC (Adapter incluso)	39W	blue, red, green, RGB (controller RGB incluso)	120°	\	cavo	Epistar	\
205		T019	400	600x600mm	100-240V AC (Adapter incluso)	39W	blue, red, green, RGB (controller RGB incluso)	120°	\	cavo	Epistar	\
206		T020	80	180x180mm	100-240V AC (Adapter incluso)	10W	blue, red, green, RGB (controller RGB incluso)	120°	\	cavo	Epistar	\
207	FARETTI LED DA INCASSO PER INTERNI ALTA POTENZA (20-24W) anche DIMMERABILI CON DIMMER TRADIZIONALI											
195		F010B	1	60Φ*25H mm, hole size dia 45mm	85-265V AC	1W	White 5500k	120°	81lm	cavo	Epiled	10W incandescenza
		F010C					Warm 3000k		76lm			
196		F0254		Φ 100*H54mm, Hole Size: Φ 70mm	100-240V AC	4W	White (6000- 7000K) Warm White(3000- 4000K)	120°	220lm	Cavo	SMD 3014	30W incandescenza





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
197		F0258		∅ 140*H61mm, Hole Size: ∅ 91mm	100-240V AC	8W	White (6000-7000K) Warm White(3000-4000K)	120°	500lm	Cavo	SMD 3014	60W incandescenza
198		F02615	1	∅ 165*H63mm, Hole Size: ∅ 140mm	110-240V AC	15W	White 6000K Warm White3000K	120°	1200-1275lm	Cavo	Epistar CRI:80	95W incandescenza
199		F02620	1	∅ 200*H77mm, Hole Size: ∅ 170mm	110-240V AC	20W	White 6000K Warm White3000K	120°	1600-1700lm	Cavo	Epistar CRI:80	120W incandescenza
200	FARETTI A LED DA INCASSO ALTA POTENZA PER INTERNI LED MODULARE											
201		F02720	1	180x180x67mm hole size 160x160mm	110-240V AC	20W	White 6000K Warm white 3000K	100°	1600-1700lm	cavo	Epistar CRI:80	100W incandescenza

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) \varnothing x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
202		F02730	1	220x220x67mm hole size 195x195mm	110-240V AC	30W	White 6000K Warm white 3000K	100°	2400-2550lm	cavo	Epistar CRI:80	2x24W CFL/ 140W incandescenza
203		F02812	1	Φ 145xDia63mm hole size Φ 125mm	110-240V AC	12W	White 6000K Warm white 3000K	100°	960-1020lm	cavo	Epistar CRI:80	85W incandescenza
204		F02820	1	Φ 196xDia63mm hole size Φ 170mm	110-240V AC	20W	White 6000K Warm white 3000K	100°	1600-1700lm	cavo	Epistar CRI:80	100W incandescenza
205		F02830	1	Φ 242xDia63mm hole size Φ 210mm	110-240V AC	30W	White 6000K Warm white 3000K	100°	2400-2550lm	cavo	Epistar CRI:80	2x24W CFL/ 140W incandescenza





LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) \varnothing x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
206	FARETTI LED DA INCASSO ORIENTABILI 90° ASSE VERTICALE, 360° ASSE ORIZZONTALE											
207		F029	1	238*148*160mm m hole size 218x130mm	AC 85-265V	25W	White 6000K Warm white 3000K	80°orientabile 90°	2125lm	cavo IP21	Epistar	alogeno 100W
208		F0308	1	108x85mm hole size size dia100mm	AC 85-265V	8W	White 6500K Warm white 3000K	80°orientabile 90°	680lm	cavo IP21	Epistar	60W incandescenza
209		F03010	1	146x110mm hole size dia138mm	AC 85-265V	10W	White 6500K Warm white 3000K	80°orientabile 90°	850lm	cavo IP21	Epistar	90W incandescenza
210		F03020	1	180x154mm hole size dia172mm	AC 85-265V	20W	White 6500K Warm white 3000K	80°orientabile 90°	1700lm	cavo IP21	Epistar	150W incandescenza



LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
211	TRACKLIGHTS ADATTABILI SU BINARIO											
212		F0313	3	53x107mm	AC 90-240V	3W	White 6000K Warm White 3000K	30°	270lm	cavo IP21	Epistar	30W alogeno
213		F0317	7	85x140mm	AC 90-240V	7W	White 6000K Warm White 3000K	30°	630lm	cavo IP21	Epistar	60W alogeno
214		F03112	12	100x185mm	AC 90-240V	12W	White 6000K Warm White 3000K	30°	1080lm	cavo IP21	Epistar	75W alogena
215		F032	1	∅ 100x130mm	AC 90-240V	24W	White 6000K Warm White 3000K	25°	2160lm	cavo IP21	CREE	90W alogena
216		F033C	1	\	AC 100-240V	25W	White 5000K	25°	2080lm	IP40	Sharp	90W alogena


LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times H$	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza	
217		F033H	1	\	AC 100-240V	25W	Warm White 3000K	25°	1900lm	IP40	Sharp	90W alogena	
218		FP0011	1 m	35,4mm(h)x32,2mm(L)	4-wire (3-phase) EU track color: white, black, grey length: 1m, 2m, 3m, 4m packing: 1m & 2m: 12pcs/box 3m: 8pcs/box 4m: 6pcs/box								
219		FP0012	2m										
220		FP0013	3m										
221		FP0014	4m										
222		FP0021	1m	35,4mm(h)x58,2mm(L)	4-wire (3-phase) recessed EU track color:white, black, grey lenth: 1m, 2m, 3m,4m packing: 1m & 2m: 12pcs/box 3m: 8pcs/box 4m: 6pcs/box								
223		FP0022	2m										
224		FP0023	3m										
225		FP0024	4m										
226		FP003					3-phase adaptor						






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
237		FP005TC										
238		FP005XC										
239	LAMPADE LED DA INCASSO NEL SOFFITTO ORIENTABILI (FARETTI E TRASFORMATORI INCLUSI)											
240		F034	3	135x135x115mm Hole Size: 110x110mm	85-265V AC	3W	White 6000K Warm White 3200K	30°	270lm	IP22	Epiled	30W alogeno
241		F035	7	205x205x130mm Hole Size: 165x165mm	85-265V AC	7W	White 6000K Warm White 3200K	30°	630lm	IP22	Epiled	60W alogeno
242		F036	12	205x205x130mm Hole Size: 165x165mm	85-265V AC	12W	White 6000K Warm White 3200K	30°	1080lm	IP22	Epiled	90W alogena

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
243		F037	6	228x126x120mm Hole Size: 205x110mm	85-265V AC	6W	White 6000K Warm White 3200K	30°	540lm	IP22	Epiled	60W alogeno
244		F038	14	390x205x130mm Hole Size: 350x165mm	85-265V AC	14W	White 6000K Warm White 3200K	30°	1260lm	IP22	Epiled	100W alogena
245		F039	9	310x130x120mm Hole Size: 280x100mm	85-265V AC	9W	White 6000K Warm White 3200K	30°	810lm	IP22	Epiled	80W alogena
246		F040	21	500x195x136mm Hole Size: 475x160mm	85-265V AC	21W	White 6000K Warm White 3200K	30°	1890lm	IP22	Epiled	
247	ARREDO URBANO Per le quotazioni vedere foglio (Illuminazione stradale)											
248		SU001	\	Φ400mm/Φ500mm	\	\	Portalamпада per arredo urbano, installazione su palo, adatto per lampadine fino a 150W, IP65, richiedere quotazione			IP65	\	\

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times$ H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
249		SU00229	24	$\Phi 560\text{mm} \times 815$ mm	100-277V AC	29W	White 6500K Commercial White 4500k Warm White 3200K	360°	1529/1426/11 47lm	IP65	CREE	
250		SU00268	54	$\Phi 560\text{mm} \times 815$ mm	100-277V AC	68W	White 6500K Commercial White 4500k Warm White 3200K	360°	3316/3102/25 68lm	IP65	CREE	
251		SU00284	72	$\Phi 560\text{mm} \times 815$ mm	100-277V AC	84W	White 6500K Commercial White 4500k Warm White 3200K	360°	4155/3870/32 06lm	IP65	CREE	
252		SU00329	24	$\Phi 560\text{mm} \times 1317$ mm	100-277V AC	29W	White 6500K Commercial White 4500k Warm White 3200K	360°	2104/1988/16 42lm	IP65	CREE	
253		SU00368	54	$\Phi 560\text{mm} \times 1317$ mm	100-277V AC	68W	White 6500K Commercial White 4500k Warm White 3200K	360°	4567/4234/35 48lm	IP65	CREE	






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
254		SU00384	72	Φ560mm×1317 mm	100-277V AC	84W	White 6500K Commercial White 4500k Warm White 3200K	360°	5705/5244/43 10lm	IP65	CREE	
255	PLAFONIERE CERTIFICATE, PER TUBI A LED PER 2 TUBI											
256		TP001	\	690*450*300mm	plafoniera da 600mm, con attacchi per 2 tubi led da 600mm	\	IP65	T8	\	\	\	\
257		TP002	\	1300*280*300 mm	plafoniera da 1200mm, con attacchi per 2 tubi led da 1200mm	\	IP65	T8	\	\	\	\
258		TP003	\	1600*280*300 mm	plafoniera da 1500mm, con attacchi per 2 tubi led da 1500mm	\	IP65	T8	\	\	\	\
259	PLAFONIERE CERTIFICATE, PER TUBI A LED PER 1 TUBO											
260		TP004	\	690*390*300mm	plafoniera da 600mm, con attacchi per 1 tubi led da 600mm	\	IP65	T8	\	\	\	\






LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
261		TP005	\	1300*300*300 mm	plafoniera da 1200mm, con attacchi per 1 tubi led da 1200mm			\	IP65	T8	\	\
262		TP006	\	1600*300*300 mm	plafoniera da 1500mm, con attacchi per 1 tubi led da 1500mm			\	IP65	T8	\	\
263	Faretti per esterno LUCE COLORATA o RGB											
264		P016	1	9x11,5x8,5 cm	85-265V AC	10W	blue, red, green, RGB (controller RGB escluso, non integrabile)	120°	800lm	Cavo IP65	Epistar	\
265		P017	1	18x14x10 cm	85-265V AC	20W	blue, red, green, RGB (controller RGB escluso, non integrabile)	120°	1600lm	Cavo IP65	Epistar	\
266	INGROUND RGB FARETTI DA INCASSO NEL TERRENO RGB, ESTERNI IP67											
267		P018	1	70,3x81mm	12V DC (adapter not included)	3W	RGB	25°/45°	IP67	Cavo		\


LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza												
268		P019		687x100mm	24V DC (adapter not included)	6W	RGB		IP67	Cavo		\												
269		P020	6	148x110mm	24V DC (adapter not included)	18W	RGB	25°/45°	IP68	Cavo		\												
270		P021	9	176x140mm	24V DC (adapter not included)	27W	RGB	25°/45°	IP68	Cavo		\												
271	FARETTI A LED MONOCOLORE (A SCELTA) DA INCASSO NEL TERRENO, PER ESTERNI IP67																							
272		P022	1	70,3x81mm	12V DC (adapter not included)	1W	<table border="1" style="font-size: small;"> <tr><td>Red</td><td>■</td></tr> <tr><td>Yellow</td><td>■</td></tr> <tr><td>Blue</td><td>■</td></tr> <tr><td>White</td><td>■</td></tr> <tr><td>Warm White</td><td>■</td></tr> <tr><td>Green</td><td>■</td></tr> </table>	Red	■	Yellow	■	Blue	■	White	■	Warm White	■	Green	■	25°/45°	IP67	Cavo		\
Red	■																							
Yellow	■																							
Blue	■																							
White	■																							
Warm White	■																							
Green	■																							
273		P023	1	70,3x81mm	12V DC (adapter not included)	3W	<table border="1" style="font-size: small;"> <tr><td>Red</td><td>■</td></tr> <tr><td>Yellow</td><td>■</td></tr> <tr><td>Blue</td><td>■</td></tr> <tr><td>White</td><td>■</td></tr> <tr><td>Warm White</td><td>■</td></tr> <tr><td>Green</td><td>■</td></tr> </table>	Red	■	Yellow	■	Blue	■	White	■	Warm White	■	Green	■	25°/45°	IP67	Cavo		\
Red	■																							
Yellow	■																							
Blue	■																							
White	■																							
Warm White	■																							
Green	■																							




LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times H$	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza												
274		P024	3	70,3x81mm	12V DC (adapter not included)	3W	<table border="1" style="font-size: 8px;"> <tr><td>Red</td><td>■</td></tr> <tr><td>Yellow</td><td>■</td></tr> <tr><td>Blue</td><td>■</td></tr> <tr><td>White</td><td>■</td></tr> <tr><td>Warm White</td><td>■</td></tr> <tr><td>Green</td><td>■</td></tr> </table>	Red	■	Yellow	■	Blue	■	White	■	Warm White	■	Green	■	25°/45°	IP68	Cavo		\
Red	■																							
Yellow	■																							
Blue	■																							
White	■																							
Warm White	■																							
Green	■																							
275		P025	6	148x110mm	24V DC (adapter not included)	18W	<table border="1" style="font-size: 8px;"> <tr><td>Red</td><td>■</td></tr> <tr><td>Yellow</td><td>■</td></tr> <tr><td>Blue</td><td>■</td></tr> <tr><td>White</td><td>■</td></tr> <tr><td>Warm White</td><td>■</td></tr> <tr><td>Green</td><td>■</td></tr> </table>	Red	■	Yellow	■	Blue	■	White	■	Warm White	■	Green	■	25°/45°	IP68	Cavo		\
Red	■																							
Yellow	■																							
Blue	■																							
White	■																							
Warm White	■																							
Green	■																							
276		P026	1	$\varnothing 60$ mm	AC 100-240V/ DC24V	2W	White (85lm)	10/25/40 /60°	IP67	Cavo	CREE	\												
277		P027	3	$\varnothing 90$ mm	AC 100-240V/ DC24V	4,2W	White (248lm)/RGB	25°/40°	IP67	Cavo	CREE	\												
278		P028	24	$\varnothing 240$ mm \times 185 mm	AC 100-240V/ DC24V	27,8W	White(1072lm)/R GB	25°/40°	IP67	Cavo	CREE	\												

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) $\varnothing \times$ H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza		
279	SEGNAPASSO DA GIARDINO													
280		SU004	3	$\Phi 208\text{mm} \times (400/600/800)\text{mm}$	100-240V AC	10,5W	White/Red/Blue/ Green			IP65		\		
281		SU005	3	188mm \times 185mm \times (400/600/800)mm	100-240V AC	10,5W	White(279lm)/Red/Blue/Green			IP65	CREE	\		
282		SU006	3	$\Phi 208\text{mm} \times (400/600/800)\text{mm}$	100-240V AC	10,5W	White(206lm)/Red/Blue/Green			IP65	CREE	\		
283	ACCESSORI													
284		V001	Ranges: 1 to 50,000 LUX; Sampling Time: 0.5 second; Accuracy: $\pm 4\%$ rdg $\pm 0.5\%$ f.s.($\pm 5\%$ rdg; Dimension: 116 \times 70 \times 29mm Operating Humidity: less than 70%R.H. Operating temperature: 0 $^{\circ}$ C to 40 $^{\circ}$ C(32 $^{\circ}$ F to 104 $^{\circ}$ F) Data-Hold function for holding measuring values											
285		V002	regolatore di carica 10A 12/24V											

LedLine LISTINO GENERALE

No.	Picture	Order Code	LED (pcs)	Size (mm) ø x H	Voltage	Watt	Color (k)	Beam Angle	Lm	Base	LED Brand	Corrispondenza
286		V003			regolatore di carica 10A 12/24V con crepuscolare							
287		V004			regolatore di carica 10A 12/24V		per due batterie					
288		V005			regolatore di carica 20A 12/24V							